

H3061P-4 230Vac/8A - kopie - kopie

Model: H3061P-4

Temperature and Humidity sensor with 25 bar pressure sensor
 1 or 2 or 4 sensors
 1 or 2 or 4 sensors



Specifications

| | |
|-----------------------|---|
| Power supply | 250Vac, 8A |
| Power consumption | Standby - Sleep |
| Humidity range | 0 to 100% |
| Humidity accuracy | ±2.5% RH from 5 to 95% at 23°C |
| Temperature range | ±0.4°C -30 to +100°C ±0.4% from reading over +100°C |
| Temperature accuracy | ±0.4°C |
| Temperature range | -30 to +80°C |
| Temperature accuracy | 1.5°C at +10°C to +25°C |
| Temperature accuracy | 2.0°C at +0°C to +25°C |
| Temperature accuracy | 3.0°C at -10°C to +25°C |
| Temperature accuracy | 6.0°C at -20°C to +25°C |
| Humidity accuracy | ±1.5g/m ³ at T < 25°C, 0 to 400 g/m ³ |
| Humidity accuracy | ±2g/kg at T < 35°C, 0 to 550 g/kg |
| Humidity accuracy | ±2g/kg at T < 35°C, 0 to 995 g/kg |
| Humidity accuracy | ±3kJ/kg at T < 25°C, 0 to 995 kJ/kg |
| Temperature range | -30 to +80°C |
| LCD display | Temperature +70°C, Humidity +70°C, LCD |
| Operating temperature | -30 to +125°C |
| Resolution | 0.025mm - 0.1mm |
| IP rating | IP65 front, IP40 back |
| Voltage | 110 to 240V / 50Hz to 60Hz |
| Current | 230 VAC - max 70 mA, 115 VAC - max 120 mA |
| Dimensions | G1/2" O.D. |
| Weight | 1m, 2m or 4m cable |
| Size | 136 x 161 x 45 mm (W x H x D), depth 150 mm, hole 18mm |
| Weight | max 490g - 1m cable |

