

T0610

□□: T0610



□□□□ 0.1°C □□□□□ 10□□□□□ □□□□□ -20 to +60°C IP□□□ IP30 LAN□ RJ-45□□□10Base-T□100Base-TX □□□ WWW, ModbusTCP, SNMPv1, SOAP □□□ E-mail (□SMTP□)□SNMP Trap□Syslog □□□□□ T-Sensor, Telnet, keyboard □□ POE□□□□IEEE 802.3af□□□5V dc□□□ □□□ □□□□, □□5.5 x 2.1 mm □□ 136 x 179 x 45mm (W x H x D), □□53 mm □□ □□320g		
2s		±0.6°C
Common	000	0.1°C
Company Com	0000	2s
IP30		000000
LAN RJ-45 100 <td< th=""><th></th><th>-20 to +60°C</th></td<>		-20 to +60°C
□□□□ WWW, ModbusTCP, SNMPv1, SOAP □□□□ E-mail (□□SMTP□□)□SNMP Trap□Syslog □□□□□□□ T-Sensor, Telnet, keyboard □□□ POE□□□□IEEE 802.3af□□□5V dc□□□□ □□□□ □□□□, □□5.5 x 2.1 mm □□□ 136 x 179 x 45mm (W x H x D), □□53 mm □□□ □□320g	IPOOO	IP30
E-mail (SMTP SNMP Trap Syslog T-Sensor, Telnet, keyboard POE SEE 802.3af SOURCE SOUR	LAN	RJ-45□□□10Base-T□100Base-TX
□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□	0000	WWW, ModbusTCP, SNMPv1, SOAP
□□ POE□□□□IEEE 802.3af□□□□5V dc□□□□ □□□□ □□□□ □□□□ FOE□□□□□ 5V dc□□□□ □□□□ □□5.5 x 2.1 mm □□3.5 x 2.1 mm □□3.5 x 2.1 mm □□3.20g □□□□ □□3.20g □□3	0000	E-mail ([[SMTP]])[SNMP Trap[Syslog
□□□□		T-Sensor, Telnet, keyboard
□□ 136 x 179 x 45mm (W x H x D), □□53 mm □□320g		POEDDDDIEEE 802.3afDDD5V dcDDD
□□ □□320g	0000	□□□□, □□5.5 x 2.1 mm
	00	136 x 179 x 45mm (W x H x D), □□53 mm
00 30	00	□□320g
	00	3[]