T6541 - □□CO2□□□□□□□□□□□□□□□□□□

□□: T6541



CO2□□□□□□□□□□T□□□□□□□□□□□□□□

Web Sensor with built-in CO_2 concentration, relative humidity and temperature sensors.

A multiple point CO_2 and temperature adjustment procedure leads to excellent CO_2 measurement accuracy over the entire temperature working range; this is a must for process control and outdoor applications. The dual wavelength NDIR CO_2 sensing procedure compensates automatically for ageing effects. The CO2 module is highly resistant to pollution and offers maintenance free operation and outstanding long term stability.

High precision capacitive polymer sensor ensures excellent long term calibration stability and ultimate accuracy. Dual line LCD is an advantage. Measured values are also converted to other humidity interpretation: dew point temperature, absolute humidity, specific humidity, mixing ratio and specific enthalpy.

The CO_2 concentration is shown on the display or signaled by a color LED.

Processing and analysis of measured data:

- online in COMET Cloud
- COMET Database software
- integration into 3-party systems

□□□□

□□	□□□
□□□□	CO2+□□+□□□□
□□□□	□□□□
□□	□□
□□□□□□	
□□□□□	□
□□□□	□
LCD□□□	□
PoE	□
CO2□□□□□□	0□10000ppm
CO2□□□□□□	±(100ppm +5%□□) at 25°C and 1013hPa
□□□□□□□□	0 to 100%
□□□□□□□□	±2.5%rH□5-95%□23°C
□□□□□□	0.6°C
□□□	0.1°C□0.1%RH□1ppm
□□□□□□□□□	2s
CO2□□□□	15s

□□□	□□□□□□□□□□□□□□□□□□□□□□□□□□□□
□□□□	□□□□□□□□
□□□□□□□□□□□□□- □□□□□□□□□□□□□□	±1.5°C□□□□□T□25°C□□□□30%□□□-60 to +80°C
□□□□□□□□□□□□	□□□□□□□
□□□□□□□	-30□+60°C
IP□□□□	IP30
LAN□□	RJ-45□□□□10Base-T□□100Base-TX
□□□□	WWW□ModbusTCP□SNMPv1□SOAP□XML
□□□□	Email□SNMP Trap□Syslog
□□	T-Sensor□WWW□□
□□	9-30Vdc□□□□□1W
□□□□□	□□□□□5.5 x 2.1mm
□□□□□□	1□□2□□□4□□□
□□	88.5 x 147.5 x 39.5mm (W x H x D)
□□	□□160g
□□	3□