U3120M □□□□□□□□□□□□□□□□□GSM□□ - kopie

□□: U3120G



4G datalogger is designed to record temperature and humidity from built-in sensors. In case of exceeded set limits, SMS and JSON messages can be sent via GPRS data connection. Measured values can be sent to the internet storage COMET Cloud, which is a complete monitoring, alarm and analysis system.

It is also possible to set the regular sending of JSON messages to COMET Database, the sending interval is adjustable. Alarms are also indicated locally by LED, LCD and acoustically by built-in beeper.
The recording is performed in a non-volatile electronic memory. The data can be transferred to a PC via included USB-C cable.

The device **includes Traceable calibration certificate** with declared metrological traceability of etalons is based on requirements of **EN ISO/IEC 17025 standard.**

□□□□

□□□□□□□	-20 to +60°C
□□□□	□□□□
□□□□□□□	±0.4°C
□□□□□□	0.1°C
□□□□□□□□□t90□□□□□□20°C□□□□□□1m/s□	8 min
□□□□□□□□□	0 to 100%
□□□□□□□□□	±1,8%**
□□□□□□□□□□□t90 □□□□□□30%rH□□□□	50 s
□□□□□□□□□	-60 to +60°C***
□□□□□	□□□□□□□□□□□□□□□□□□
□□□□□□□	1s □ 24h□□
□□□□□□□□	1 s, 10s, 1min□□
□□□□□□	500 000□□□□□□□□□□□□□□□350 000□□□□□□□□□□□□
□□□□□□□	□□□ - □□□□□□□□□□□□□□□ - □□□□□□□□□□□□□□□□□□
□□	□□□□□□□□5200mAh
IP□□□□	IP67 electronics; IP30 sensors
□□	61x93x53□□□□□□120x93x53
□□□□□□□	260 g
□□	3□